



SBRS
A Member of the Shell Group

Shell Recharge

Mobile Charger Flex

The **Flex mobile chargers** from SBRS are portable, making it deployable in any location. It's a powerful, full-size charging solution for ensuring you can **charge up wherever you go**.

TWO MODELS AVAILABLE

1

Mobile charger for continuous charging of heavy commercial vehicles.

MEASUREMENTS*

H: 1400mm (on rolls)

W: 800mm

D: 600mm

*Measurements excl. cable



2

Mobile charger for highly flexible workshop operation.

MEASUREMENTS*

H: 955mm (on rolls)

W: 560mm

D: 650mm

*Measurements excl. cable



CHARGING POWER

80 kW (125A)
40kW (63A)
20kW (32A)



MAXIMUM CURRENT

200 A



CONTINUOUS OUTPUT POWER

80 kW



CHARGING VOLTAGE

200 V to 1,000 V




PLUG & PLAY INSTALLATION

Just connect the standard CEE plug, switch on the charger, and connect the charging plug to your vehicle.



CUSTOMIZABLE CHARGING

You have the power to select your preferred charging settings or terminate the charge when you want. The display also shows detailed charge data for your convenience.



EXTREME TEMPERATURE COMPATIBILITY

Our charger can handle extreme temperatures, from -25°C to +45°C, ensuring reliable performance in various weather conditions. It comes with IP44/IP54 protection class for added durability.



SEAMLESS COMMUNICATION

Communicate with your vehicle effortlessly via the CCS Combo 2 connector, meeting DIN 70121/ISO 15118 standards. Our charger also boasts a communication interface via LTE, connecting the backend for remote monitoring.



ROBUST SAFETY FEATURES

With short-circuit and no-load protection, integrated load monitoring, and a service connection for laptop, Ethernet, LTE (optional SIM card required) and display, you can trust in the safety and reliability of our charger.

SUITABLE FOR:



E-TRUCKS



E-BUSES



E-VANS

www.sbrs.com